



Cement based Coarse Putty

Cement based coarse putty is more durable & has better adhesion strength compared to other conventional products.

PRODUCT DESCRIPTION

Coarse Putty specially developed as a base coat to cover unevenness and pinholes in the plastered surface to the walls/ceilings ready for final application. As it is white, it can be treated as a base coat for putty. Wall putty contains finest quality minerals, white cement and polymers.

Packing Availability: 40kg.

| Sr. No. | Test | Specification |
|---------|-------------------------|---|
| 1. | Appearance | Powder form |
| 2. | Colour | White |
| 3. | Odour | Mild phenolic smell |
| 4. | Solubility | Completely miscible with water |
| 5. | pH | 8 – 9 |
| 6. | Drying time | Touch Dry – 2-3 hours Recoat – 10-12 hours |
| 7. | Thickness | 1 st -3-4 mm per coat 2 nd -3-4 mm per coat Total 6-8 mm/2 coat |
| 8. | Covering | 120-130 sqft/40kg/2 coats 8mm |
| 9. | Application | By putty knife/mason's steel trowel |
| 10. | Shelf life | 6 months |
| 11. | Finish | Rough finish |
| 12. | Alkali resistance | Excellent |
| 13. | Water permeability | Excellent |
| 14. | Relative density (28°C) | 1.35 – 1.45 kg/lit |
| 15. | Water intake | 25-30% |

For more information, visit www.gardwelindustries.com

