



FIRST CHOICE DISTEMPER

First Choice Distemper can be used as a whitewash as well as for interior coatings as a decorative paint. Distempered surfaces cannot be easily washed down and last longer on interior surfaces. It is cheaper than oil paint.

MOST IMPORTANT CHARACTERISTICS:

- Smooth finish • Very good attachment • Ecological friendly • Odourless •
- Low VOC

PACKING AVAILABILITY: 20 kg, 10kg, 5 kg and 1 kg packing.

SHELF LIFE: 12 months in seal packed container

Sr. No.	Test	Specification
1	Appearance	Viscous liquid in paste form
2	Colour	Super white
3	Odour	Mild
4	Solubility	Completely miscible with water
5	Viscosity	140 KU
6	Drying time	Touch dry- 25-30 Minutes Recoat- 4-5 hours
7	Thickness	10 micron per coat
8	Covering	900-1000 sq.ft/20 kg with two coat
9	Application	By brush/roller/spray
10	Life of paint	3 years
11	Finish	Smooth and matt
12	Alkali resistance	Excellent
13	Water permeability	Excellent
14	Relative density (20°C)	1.7-1.8 kg/lit
15	Water intake	50-60%
16	pH	8-9.5
17	Solids by weight	65-70%

Gardwel Industries

78/1, Choudhary Industrial Estate, Mouje Shivane, New Ahiregoan, Pune - 411023

For more information, visit www.gardwelindustries.com or call +91-94220-20385/485