



## PURE ACRYLIC EMULSION

**Silk Touch Pure Acrylic Emulsion** is capable of giving any desired finish such as gloss with rich finish. Customized shades are possible.

**PACKING AVAILABILITY:** 20 lit, 10 lit, 4 lit packing.

**PRELIMINARY PREPARATION OF SURFACE:** Surface should be free from any loose dust. With properly plastered with one coat of primer

**SHELF LIFE:** 12 months in seal packed container

Sr. No.	Test	Specification
1	Appearance	White smooth viscous paste
2	Colour	White ,coloured as per required
3	Solubility	Completely soluble with water
4	Application	By roller, Brush
5	Water demand	25-30%
6	Drying Time	Touch dry- 2 hour Recoat- 6 to 8 hours
7	Thickness	30-50 micron per coat
8	Covering	65-75 sq.ft/lit per coat
9	Viscosity	125-130 KU at 30 deg
10	VOC Content	25-30% by weight
11	Finish	Smooth and glossy

**Lead and Mercury content does not exceed 90 parts per million**

Gardwel Industries 78/1, Choudhary Industrial Estate, Mouje Shivane, New Ahiregoan, Pune - 411023  
For more information, visit [www.gardwelindustries.com](http://www.gardwelindustries.com) or call +91-94220-20385/485

---