



SILK TOUCH ACRYLIC WATER PRIMER

Silk Touch Acrylic Water Primer is specially designed economical primer to adhere surfaces and to form a binding layer that is better prepared to receive the paint. Priming ensures better adhesion of paint to the surface, increases paint durability, and provides additional protection for the material being painted.

PACKING AVAILABILITY: 20 lit, 10 lit, 4 lit and 1 lit packing.

SHELF LIFE: 12 months in seal packed container

Sr. No.	Test	Specification
1	Appearance	Viscous liquid in paste form
2	Colour	White
3	Odour	Mild
4	Solubility	Completely miscible with water
5	Viscosity	110+/-5 KU
6	Drying time	Touch dry- 25-30 Minutes Recoat- 5 to 6 hours
7	Thickness	10-20 micron per coat
8	Covering	70-80 sq.ft/lit per coat
9	Application	By brush/roller/spray
10	Shelf life	1 years
11	Finish	Smooth and matt
12	Alkali resistance	Excellent
13	Water permeability	Excellent
14	Relative density (20°C)	1.50-1.60 kg/lit
15	Water intake	40-50%
16	pH	8-9.5
17	Solids by weight	50+/-4%

Gardwel Industries

78/1, Choudhary Industrial Estate, Mouje Shivane, New Ahiregoan, Pune - 411023

For more information, visit www.gardwelindustries.com or call +91-94220-20385/485

For more information, visit www.gardwelindustries.com or call +91-94220-20385/485