



SILK TOUCH INTERIOR/EXTERIOR EMULSION

Silk Touch Interior/Exterior Emulsion is specially design for giving finishes such as matt, rich look with desired coverage with economical range. Customized shades are possible.

APPLICABLE AREA: Interior or Exterior wall surface

PACKING AVAILABILITY: 20 lit, 10 lit, 4 lit and 1 lit packing.

SHELF LIFE: 24 months in seal packed container

Sr. No.	Test	Specification
1	Appearance	Viscous liquid in paste form
2	Colour	White/tinted from base
3	Odour	Mild
4	Solubility	Completely miscible with water
5	Viscosity	108-110 KU
6	Drying time	Touch dry- 25-30 Minutes Recoat- 5 to 6 hours
7	Thickness	10-20 micron per coat
8	Covering	70-80 sq.ft/lit per coat
9	Application	By brush/roller/spray
10	Shelf life	2 years
11	Finish	Smooth and egg shell
12	Alkali resistance	Excellent
13	Water permeability	Excellent
14	Relative density (20°C)	1.40-1.50 kg/lit
15	Water intake	30-40%
16	pH	8-9.5
17	Solids by weight	55-60%

Gardwel Industries

78/1, Choudhary Industrial Estate, Mouje Shivane, New Ahiregoan, Pune - 411023

For more information, visit www.gardwelindustries.com or call +91-94220-20385/485

For more information, visit www.gardwelindustries.com or call +91-94220-20385/485