



SILK TOUCH LAQUER COAT

DETAILS:

Silk Touch Laquer Paint This water based lacquer is suitable for indoor and Outdoor use. The lacquer has a soft, matt, silk gloss

MOST IMPORTANT CHARACTERISTICS:

• Scrub resistant • Fast drying • Very good attachment • No yellowing • Ecological friendly • Odorless • Strong scratch resistant • Low VOS • Heat Resistant until max. 120°C • Best water resistance • Colorless

PACKING AVAILABILITY:

20 lit, 10 lit, 4 lit and 1 lit packing.

1q

SHELF LIFE:

12 months in seal seal-packed container

Sr. No.	Test	Specification
1	Appearance	Transparent clear liquid
2	Color	colourless
3	Odor	Mild
4	Solubility	Completely miscible with water
5	Viscosity	85-89 KU
6	Drying time	Touch dry- 25-30 Minutes Recoat- 4-5 hours
7	Covering	100-125 sq.ft/lit per coat
8	Application	By brush/roller/spray
9	Finish	Smooth and glossy
10	Water permeability	Excellent
11	Solids by weight	25-28%
12	Water intake	5-10% (if required)
13	Durability	3-5 Year (2-3 Coat)

Gardwel Industries 78/1, Choudhary Industrial Estate, Mouje Shivane, New Ahiregoan, Pune - 411023

For more information, visit www.gardwelindustries.com or call +91-94220-20385/485
