



TEX-SURE ROLLER FINISH

Tex-Sure Roller Finish is a Copolymer emulsion based exterior texture finish reinforced by marble & Quartz powder. Formulated specially for use as a decorative and protective exteriorcoating.

APPLICABLE AREA: Roller Finish applied on prepared masonry, concrete, plaster, gypsum Board

PACKING AVAILABILITY: Available in 30 kg packing

SHELF LIFE: 6 months in seal packed bag (stored in cool & dry place)

Sr. No.	Test	Specification
1	Finish	Roller Finish, Snow peaks
2	Colour	Base Colour
3	Odour	Mild
4	Thinning(by water)	Ready to use (3-5% water if required)
5	Application	By Roller/Spray Gun
6	Drying time @ 30°C	Touch dry- 30-60 minutes ,Dry to Recoat- 24 hours <u>Temperature, humidity, air movement, film thickness and number of coats all affect the drying time.</u>
7	Dry Film Thickness (DFT)	1.0 mm
8	Theoretical Covering	160-180 sq.ft/30kg bag per coat Actual spreading may vary depending on substrate condition and application method and texture pattern
9	Abrasion Resistance	Excellent
10	Alkali resistance	Excellent
11	Water Resistance	Excellent
12	Biological Resistance	Resistance to Algae and Fungi
13	Durability	2-3 years

Gardwel Industries 78/1, Choudhary Industrial Estate, Mouje Shivane, New Ahiregoan, Pune - 411023

For more information, visit www.gardwelindustries.com or call +91-94220-20385/485
