



CEMENT BASED WALL PUTTY

WallGard Cement Based Wall Putty is used on a brickwork wall to make it smooth and primer ready. It also is used to fill up the cracks and holes in the walls to make it less vulnerable for water seep damages.

PACKING AVAILABILITY: 40kg, 20kg, 5kg and 1kg packing

SHELF LIFE: 12 months in seal packed bag

PRE WET THE SURFACE BEFORE APPLICATION OF 1ST COAT OF ASIAN WALL PUTTY

Sr. No.	Test	Specification
1	Appearance	White fine powder
2	Colour	White
3	Solubility	Completely miscible with water
4	Application	By putty knife/steel trowel
5	Water demand	40-50% per coat
6	Drying Time	Touch Dry – 45-60 Min Recoat – 6-8 Hrs
7	Thickness	0.5-1.0 mm per coat
8	Covering	450-500 sq ft/40 kg bag 1.5mm thickness with two coat
9	Pot life of wet material	30-45 min
10	Water Permeability	Excellent
11	Recommended Area	Cement plaster, gypsum plaster, Concrete surface ,Interior wall

Gardwel Industries 78/1, Choudhary Industrial Estate, Mouje Shivane, New Ahiregoan, Pune - 411023
For more information, visit www.gardwelindustries.com or call +91-94220-20385/485
